

Controller Keyboard

NVCK-3X

Controller Keyboard w/ 3-Axis Joystick




Key Features

- 1 Master with 7 Slave Keyboards Support
- Internal Memory for Download/Save/Upload PTZ Settings.
This feature is only available with NUVICO PTZ Domes.
- Built-in RS-485/422 communication port enables the NVCK-3X to operate PTZ Dome Cameras & NUVICO DVRs
- Direct control of upto 256 Dome Cameras
- Half Duplex: Upto 64 ID Simplex: Upto 256 ID
- Control Upto 99 NUVICO DVRs
- 3-Axis Joystick for Pan/Tilt/Zoom with 64 Variable Speeds
- LCD Display
- User friendly design with clearly labeled operation keys
- Alarm Acknowledgement
- Keyboard Lock
- User Login Feature
- 18 Programmable Function Keys
- Real Time Clock

Specifications

Item	NVCK-3X
Communications	RS-485 / 422, RJ-45
Baud Rates	2400, 4800, 9600 & Upto 230,000 bps
Power Input	12VDC, 0.5A
Operating Temperature	0°C ~ 50°C
Humidity	0 to 90%RH (non-condensing)
Dimensions	390 x 190 x 65(mm)
Weight	1.2kg

System Configuration



NUVICO INC.

53 Smith Street, Englewood, NJ 07631-4607 USA
 Phone 201-541-1605 Toll Free 866-523-1700 Fax 201-541-1620
 sales@nuvico.com www.nuvico.com

NUVICO reserves the right to alter product offers and specification at any time without notice.
 Copyright © 2006 Nuvico. All rights reserved.

NUVICO®

Connecting Videos Anywhere™